




Safe Home Security Cheat Sheet

- Once system is fully powered up, select the GoControl! Icon at the bottom corner. Type in 1561 (default installer code).
- Select System Configuration



(NOTE: 2Gig Panels use a Question based programming. You will have to enter a 2-digit question for programming certain fields.)

REQUIRED FIELDS

Go To: Q22 (Lack of Usage) → 30
Go To: Q29 (Periodic Tests) → 7
Go To: Q43 (Installer Code) → 3825
Go To: Q57 (Restoral Reports) → 1
Go To: Q72 (Quick Bypass) → 1
Go To: Q91 (Radio Supplier) → 1(ADC)
4(Securenet)

OPTIONAL FIELDS

Go To: Q05 (Exit Delay)
Go To: Q06 (Entry Delay)
Go To: Q07 (Entry Delay 2)
Go To: Q13 (2-Way Voice)
Go To: Q66 (Day Light Savings) → 1
(Arizona & Hawaii Only)

On both ADC and Quantum CBU's, the time, date and weather will update by itself. It may require a panel reboot, but it should update all of those features automatically.

Program Duress Code

Select → Security → Menu → Toolbox → Installer Code →
User Management →
Scroll Down until you see Duress Code programming.

For Wireless Programming and labels, refer to 2GIG installation guide.